

[6] Tools required:

Socket wrench (10mm), Ratchet handle & Phillips screw driver, Scissors, Tape measure, Phillips short screw driver, Clip remover, Soft cloth

[7] INSTALLATION PRECAUTIONS/NOTES

For assurance of a safe and accurate installation, be certain to observe the following precautions.

- Before beginning the installation, the following caution must be read to carry out the installation securely and safely. When detaching parts, please refer to the vehicle service manual.
- Please note that the manufacturer of this product is not liable in the event of damage or accidents owing to usage other than that described in this instruction manual.

CAUTION

1. Prior to installation, read all sections of this installation manual to understand all procedures.
2. The side sill protectors are a resin product. Do not subject to strong shocks or unnecessary force. Also take sufficient care not to change its original shape and not to scratch the surface.
3. When handling, wear gloves to prevent injury from the edges of this product. Take sufficient care.
4. When installing this product, park the vehicle on a flat area and ensure that the hand brake is applied. If the vehicle is jacked up using other than the board-on-lift system, this makes the installation easier. Also, the ignition key must be off to ensure extra safety.
5. Be careful not to scratch this product or parts of the vehicle during installation.
6. Wipe off any dust or dirt on the vehicle where the side sill protectors are going to be installed. Use a piece of soft cloth with mild detergent.
7. When this product becomes dirty, clean it with mild detergent using a sponge. Do not use organic solvents such as thinners, etc., nor acid and alkali.
8. When painting, urethane paint for resin products must be used applying a baking finish under 80C°.
9. For a smooth installation, two technicians are needed.
10. We recommend that the side sill protectors are installed by an authorized INFINITI dealer.
11. Once the side sill protectors are installed, in the event of jacking-up the vehicle for the purpose of servicing, etc., if the board-on-lift system is going to be used, use an adapter etc., in order not to damage the side sill protectors.
12. When using steel chains, fasten bolt and screw connections tightly.